

ThoughtWorks®

IOS模块化开发实战

官勤

- 什么是模块化开发 - What
- 为什么要模块化开发 - Why
- 什么时候进行模块化开发 - When
- 如何实现模块化开发 - How

什么是模块化开发

WHAT



为什么要模块化开发

WHY

复用

解耦

独立开发测试

加快编译速度

什么时候进行模块化开发

WHEN

纵向划分技术模块的简单示意图

数据展示

View、ViewModel、Presenter等

数据处理模块（业务逻辑、Controller等）

数据请求模块（Model、Entity等）

缓存模块

数据库模块

网络通信模块

多平台

横向划分业务模块，以一电商型App为例

商品
模块

订单
模块

购物车
模块

消息
模块

支付
模块

...

技术模块作支撑

多条独立的业务线

如何实现模块化开发

HOW

业界的一些模块方案




CTMediator

Demo

Demo_Category

Framework

CocoaPods



私有Pod

```
source 'https://github.com/CocoaPods/Specs.git'  
  
platform :ios, '9.0'  
target 'App' do  
  use_frameworks!  
  
  pod 'PublicPod', '0.2.0'  
  
end
```

私有Spec Repo


```
pod repo add PrivateSpecs https://private.git
```

~/.cocoapods/repos

更新podspec版本号到1.0.0

```
git commit
```

```
git tag -m "first release" 1.0.0
```

```
git push 1.0.0
```

```
pod repo push --allow-warnings
```

```
PrivateSpecs demo.podspec
```

```
source 'https://github.com/CocoaPods/Specs.git'  
source 'PrivatePodSpecRepo.git'  
  
platform :ios, '9.0'  
target 'App' do  
  use_frameworks!  
  
  pod 'PublicPod', '0.2.0'  
  pod 'Demo', '1.0.1'  
  pod 'Demo_category', '1.0.0'  
  
end
```

Nightmare

```
Pod::Spec.new do |s|
  s.name           = "App function"
  s.version        = "0.0.3"
  s.platform       = :ios, "9.0"
  s.source         = { :git => "appfunction.git", :tag => s.version.to_s }
  s.dependency    "Demo_category", "1.0.0"
```

```
source 'https://github.com/CocoaPods/Specs.git'  
source 'PrivatePodSpecRepo.git'  
  
platform :ios, '9.0'  
target 'App' do  
  use_frameworks!  
  
  pod 'PublicPod', '0.2.0'  
  pod 'Demo', :git => 'demo.git', :tag => '1.0.1'  
  pod 'Demo_category', '1.0.0'  
  
end
```


二进制化

CocoaPods Packager

Carthage

Shell

sub spec

```
s.version = "1.0.0"
s.source = { :git => "https://demo.git", :tag => s.version.to_s }
s.default_subspec = 'source'

s.subspec 'source' do |ss|
  ss.source_files = 'Demo/Demo/* */*'
end

s.subspec 'framework' do |ss|
  ss.vendored_frameworks = 'Demo/Framework/*.framework'
end
```

```
pod 'Demo', '1.0.0'
```

```
pod 'Demo/framework', '1.0.0'
```

公有Pod的二进制化

prepare_command

Development Pod


```
source 'https://private.git'  
source 'https://github.com/CocoaPods/Specs.git'  
  
platform :ios, '9.0'  
  
target 'App' do  
  use_frameworks!  
  
  pod 'PublicPod', '0.2.0'  
  
  if ENV['dev']  
    pod 'Demo', :path=>'../Demo'  
  else  
    pod 'Demo/framework', '1.0.0'  
  end  
end  
end
```

dev=1 pod install

CI/CD

依赖管理

Show Time

Q & A

THANK YOU

官勤